PØ15

P 42499 US

Claims

-8-

- 1. An arrangement for attaching a shower fixture having a vertical rod to be mounted on a wall, a holder for a shower head having a hose, where the holder is attached to the rod (1), a guide for the shower hose (9) being configured such that it the guides the shower hose from its fitting connecting it to the shower head at least to the vicinity immediately adjoining the rod.
- 2. An arrangement according to claim 1, where the hose guide is configured such that the hose may be inserted and withdrawn without actuating any components.
- 3. An arrangement according to claim 1, where at least part of the hose guide is arranged on the holder for the shower head.
- 4. An arrangement according to claim 1, where the shower hose is held in place on an arch bridging the transition to the vertical rod.
- 5. An arrangement according to claim 1, where at least part of the hose guide is formed on the rod.
- 6. An arrangement according to claim 1, where the hose guide has a groove for accommodating the shower hose arranged in, or on, the rod.
- 7. An arrangement according to claim 6, where the groove opens out onto the front surface of the rod.
- 8. An arrangement according to claim 6, where the cross-section of the groove is larger than the cross section of the hose.

P 42499 US

-9-

- 9. An arrangement according to claim 6, where the groove is undercut and the width of the slot is slightly less than the diameter of the hose.
- 10. An arrangement according to claim 1, where the guide for the shower hose has means for securing the hose that make its withdrawal from the holder more difficult situated at at least one location on the rod.
- 11. An arrangement according to claim 10, where the means for securing the hose has a deformable and/or pivotable element.
- 12. An arrangement according to claim 10, where the means for securing the hose has a change in the cross-section of the groove.
- 13. An arrangement according to claim 10, where the means for securing the hose has a tapering of the slot leading into the groove.
- 14. An arrangement according to claim 10, where the means for securing the hose is arranged in the vicinity of the lower end of the rod.
- 15. An arrangement according to claim 10, where the means for securing the hose is arranged in a terminating element that may be attached to the lower end of the rod.
- 16. An arrangement according to claim 6, where the holder for the shower head is mounted on a translatable slide and the guide-groove for the slide forms the groove for accommodating the hose.